



GLOCK 21 Gen5/MOS/FS



FRONT SIGHT
polymer



SLIDE STOP LEVER
ambidextrous

TRIGGER CONFIGURATION
triggerspring01 / connector 5 /
firing pin spring 24N (silver)



REAR SIGHT
polymer



MAGAZINE
13 rds



MAGAZINE CATCH
reversible



Technical data are rounded and do not reflect any tolerances – they may be altered without notice.

www.glock.com



DIMENSIONS

	mm	in.
1. LENGTH (OVERALL)	205	8,07
2. SLIDE LENGTH (cpl.)	191	7,52
3. WIDTH (OVERALL)	35	1,38
4. SLIDE WIDTH	28,5	1,12
5. HEIGHT INCL. MAGAZINE	140	5,51
6. SIGHT RADIUS (POLYMER)	176	6,93
SIGHT RADIUS (STEEL)	175	6,89
SIGHT RADIUS (GNS)	174	6,85
7. TRIGGER DISTANCE	72,5	2,85
8. BARREL DISTANCE	20	0,79

VARIABLE DIMENSIONS

		mm	in.
MEDIUM BACKSTRAP w/o beaver tail (+ 2 mm 0.08 in.)	1. LENGTH (OVERALL)	207	8,15
	7. TRIGGER DISTANCE	74,5	2,93
LARGE BACKSTRAP w/o beaver tail (+ 4 mm 0.16 in.)	1. LENGTH (OVERALL)	209	8,23
	7. TRIGGER DISTANCE	76,5	3,01

TECHNICAL DATA



CALIBER

.45 Auto



MAG. CAPACITY

13 rds



BARREL PROFILE

octagonal



BARREL LENGTH

mm	in.
117	4,61



LENGTH OF TWIST

mm	in.
400	15,75



WEIGHT

without magazine	
g	oz
735	25,93



WEIGHT

with empty magazine	
g	oz
825	29,10



WEIGHT*

with loaded magazine	
g	oz
1095	38,62



TRIGGER TRAVEL

mm	in.
12,5	0,49

TRIGGER PULL

N	lbf
26	5,8

* depending on the ammunition used